ECANO2

CONTACTLESS CAN READING ACCESSORY

CONTACTLESS   EASY TO MOUNT

TELTONIKA | Telematics

ECANO2

E 57 10R-06 1673

CONTACTLESS

ECANO2 collects vehicle data from CAN bus without damaging the wires.

POWERED

Powered from an on-board power source.

SIGALS READING

Reads the signals through the isolation of CAN bus wires.

EASY TO INSTALL

Easy to install and operate

LIGHT VEHICLES

TRUCKS

SPECIAL TRANSPORT

INTERNATIONAL LOGISTICS

ECANO2 is a new and small warranty friendly adapter for reading CAN data in contactless mode.

19 mm

39 mm

12 mm

Technical data

Supported by	LV-CAN200, ALL-CAN300, FMB630, FMX640, FMB641, FMB140, FMB240, FMX150, FMX650
Input Voltage range	10 - 30 V DC
Power consumption	At 12 V < 1,7 mA (Standby) At 12 V < 7,5 mA (Working)
Operating temperature range	40°C to +85°C
Operating humidity	Max 85% non-condensing
Features	Contactless CAN reading Warranty friendly CAN-BUS speed up to 1000 kb/s
Dimensions	39 x 19 x 12 mm (L x W x H)